

SPC1530

Super Pulse Battery Capacitor

1. Scope

This data sheet describes the mechanical design and performance of EVE (Super Pulse Battery Capacitor) model SPC1530, optimized for extreme temperatures, used in an ER+SPC battery system.

2. Key features

- ◆ High power capacity
- ◆ Delivering high current pulses
- ◆ Long operating life
- ◆ Wide operating temperature range
- ◆ Extremely low self-discharge
- ◆ High security and reliability

3. Mechanical characteristics

Length 27.0 mm. Max
 Diameter 15.1 mm. max
 Weight 10.1 gr. max

4. Electrical characteristics

4.1 Nominal voltage: 3.6V (3.9V Max)

4.2 Discharge

4.2.1 Nominal capacity (RT)

When charged to 3.67V: 290 A*sec

Cut-off discharge voltage: 2.5V

(Discharge below 2.5V at RT and discharge below 2.0V at -40°C may increase the SPC internal impedance)

4.2.2 Maximum discharge current

Continuous: 0.75A

Pulse: 3.0A

4.3 Charge (constant current)

Max. charge voltage: 3.95V

Max. charge current: 50mA

4.4 Internal impedance

≤140 mOhm (RT @ 1kHz)

4.5 Self discharge in ER+SPC battery

at RT: 1.8µA at 80°C: 8µA

5 Temperature range

Test Item	SPC1530 used independently	In ER+SPC battery system
Operating Temperature	-40°C to 85°C	-40°C to 85°C
Storage Temperature	-30°C to 60°C	-30°C to 60°C

4.6 Shelf life

Shelf life at different storage temperature to 80% of initial capacity.

Temperature	SPC1530
RT	1 year
60°C	2 weeks
80°C	1 week

4.7 Number of charge-discharge cycles to 80% of initial

	100% DOD	10% DOD	1% DOD
Charge to 3.67V	2000	20000	200000
Charge to 3.90V	1000	5000	50000

DOD: Depth of Discharge

4.8 Safety tests

The SPC successfully passed the following tests:

- Short circuit at RT and 55°C
- Compression
- Impact
- Overcharge
- High temperature exposure
- Shock and Vibration
- Nail penetration
- Forced discharge



EVE Capacitors performed the tests according to UL 1642 specification for lithium batteries.

Lithium content of SPC1530 is less than 0.1 gr., it is not restricted for air transportation.


Warning:

- The SPC1530 is designed for use in a ER+SPC battery system or in low charge current as specified only.
- The SPC1530 may explode or violently vent if over-charge above 4.4V.
- Do not charge the SPC1530 higher than 4.1V, over discharge, short circuit, heat above 100°C, incinerate or expose content to water.
- Charging the SPC1530 at above 3.95V may lead to capacity loss and / or internal impedance rise.

6. Performance data



Discharge capacity vs. OCV for SPC1530 (at RT, 90mA discharge)



Note

All datas in this datasheet are laboratory test results. It is for reference only and not intended as a technical or quality assurance voucher.